

1010-RDP	DRAWN BY: CR	CHECKED BY: CR	APPROVED BY: CR	DATE: 02-10-2006	SCALE: NONE	SIZE: A	DRAWING NUMBER: S1010-RDP	I	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com ASPE MEMBER OF: LOCATION																																																													
									SPECIAL PURPOSE ROOF DRAIN LOW PROFILE DOME WITH DECK PLATE																																																													
									*This Dimension to Internal Shop of Speedi-Set® Gasket. Recommended Deck Opening 17(430)DIA Fig. 1010Y-RDP..... NO-HUB OUTLET Fig. 1010C-RDP..... CAULK OUTLET **NOTE: 08(200) & 10(250) outlet sizes are regularly furnished with 20(510) dia. flange. If 16(405) dia. flange is required -16 MUST be specified. Ex: 1010Y08-16 or 1010Y10-16 ▲ NOTE: The dome height is 8 1/4" (210) for the 122.5 SQ IN free area dome and is regularly furnished in Cast Iron and is not available in polyethylene.																																																													
									<table><tr><th>A SIZE</th><th>B CAULK, NO-HUB, & SPEEDI-SET®</th><th>THREADED</th><th>C*</th><th>D DIA</th><th>E DIA</th><th>F</th><th>G</th><th>FREE AREA SQ IN</th></tr><tr><td>02(50), 03(75) or 04(100)</td><td>5(125)</td><td>3 3/4(95)</td><td>3 3/4(95)</td><td>15 1/4(390)</td><td>11(280)</td><td>24(610)</td><td>5 1/4(133)</td><td>102.5(661)</td></tr><tr><td>05(125) or 06(150)</td><td>5(125)</td><td>3 3/4(95)</td><td>--</td><td>15 1/4(390)</td><td>11(280)</td><td>24(610)</td><td>5 1/4(133)</td><td>102.5(661)</td></tr><tr><td>**08(200)-16,</td><td>6</td><td>5</td><td>--</td><td>16</td><td>12 1/2</td><td>24</td><td>5 1/4(133)</td><td>102.5 (661)</td></tr><tr><td>**10(250)-16</td><td>(150)</td><td>(125)</td><td>--</td><td>(405)</td><td>(320)</td><td>(610)</td><td>8 1/4(210)</td><td>122.5 (790)</td></tr><tr><td>08(200), 10(250), or 12 (300)</td><td>7 3/4(195)</td><td>7 3/4(195)</td><td>--</td><td>20(510)</td><td>16(405)</td><td>28(711)</td><td>7 1/4(185)</td><td>228(1471)</td></tr></table>								A SIZE	B CAULK, NO-HUB, & SPEEDI-SET®	THREADED	C*	D DIA	E DIA	F	G	FREE AREA SQ IN	02(50), 03(75) or 04(100)	5(125)	3 3/4(95)	3 3/4(95)	15 1/4(390)	11(280)	24(610)	5 1/4(133)	102.5(661)	05(125) or 06(150)	5(125)	3 3/4(95)	--	15 1/4(390)	11(280)	24(610)	5 1/4(133)	102.5(661)	**08(200)-16,	6	5	--	16	12 1/2	24	5 1/4(133)	102.5 (661)	**10(250)-16	(150)	(125)	--	(405)	(320)	(610)	8 1/4(210)	122.5 (790)	08(200), 10(250), or 12 (300)	7 3/4(195)	7 3/4(195)	--	20(510)	16(405)	28(711)	7 1/4(185)	228(1471)
									A SIZE	B CAULK, NO-HUB, & SPEEDI-SET®	THREADED	C*	D DIA	E DIA	F	G	FREE AREA SQ IN																																																					
02(50), 03(75) or 04(100)	5(125)	3 3/4(95)	3 3/4(95)	15 1/4(390)	11(280)	24(610)	5 1/4(133)	102.5(661)																																																														
05(125) or 06(150)	5(125)	3 3/4(95)	--	15 1/4(390)	11(280)	24(610)	5 1/4(133)	102.5(661)																																																														
**08(200)-16,	6	5	--	16	12 1/2	24	5 1/4(133)	102.5 (661)																																																														
**10(250)-16	(150)	(125)	--	(405)	(320)	(610)	8 1/4(210)	122.5 (790)																																																														
08(200), 10(250), or 12 (300)	7 3/4(195)	7 3/4(195)	--	20(510)	16(405)	28(711)	7 1/4(185)	228(1471)																																																														
REGULARLY FURNISHED: Duct Cast Iron Body with attached Deck Plate with Securing Holes, combined Flashing Clamp and Gravel Stop with Polyethylene Dome. NOTE: Dimensions shown in parentheses are in millimeters. VARIATIONS: ☐ L Speedi-Set® Service Weight Outlet Conn. (02, 03, and 04) Sizes Only ☐ LXH Speedi-Set® Extra Heavy Duty Outlet Conn. (02, 03, and 04) Sizes Only ☐ T Threaded Outlet Conn. Extension (Specify Height) -E ☐ Secondary Flashing Clamp -C2 ☐ Vandal Proof Dome -U OPTIONAL MATERIALS: ☐ Aluminum Dome -AD ☐ Cast Iron Dome -CID ☐ Galvanized Cast Iron Dome -CIDG ☐ Galvanized Cast Iron Body & Collar -G ☐ Rough Bronze Dome -RBD ☐ Stainless Steel (Specify Fig. 9780) ▲▲ Optional Domes' free area are as follows: <table><tr><th>Dome Mat'l</th><th>02-06 Outlets</th><th>08 & 10 Outlets</th></tr><tr><td>Aluminum</td><td>98 (632)</td><td>150 (968)</td></tr><tr><td>Cast Iron</td><td>80 (516)</td><td>Reg. Furnished</td></tr><tr><td>Bronze</td><td>95 (613)</td><td>150 (968)</td></tr></table>								Dome Mat'l	02-06 Outlets	08 & 10 Outlets	Aluminum	98 (632)	150 (968)	Cast Iron	80 (516)	Reg. Furnished	Bronze	95 (613)	150 (968)																																																			
Dome Mat'l	02-06 Outlets	08 & 10 Outlets																																																																				
Aluminum	98 (632)	150 (968)																																																																				
Cast Iron	80 (516)	Reg. Furnished																																																																				
Bronze	95 (613)	150 (968)																																																																				