













G	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: LOCATION 																																																																	
	FLOOR OR SHOWER DRAINS WITH ADJUSTABLE STRAINER HEADS																																																																	
	A (Pipe Size) = 02(50), 03(75), 04(100), 05(125) or 06(150)																																																																	
SIZE A	SCALE: NONE																																																																	
DRAWING NUMBER S2005(-UDC)	DATE: 09/02/05																																																																	
APPROVED BY: CL																																																																		
CHECKED BY: CL																																																																		
DRAWN BY: JJ																																																																		
NO-HUB OUTLET ☐ Fig. 2005Y(-UDC).....(A) ROUND TOP ☐ Fig. 2005Y(-UDC).....(B) SQUARE TOP <table border="1" style="font-size: 0.8em;"> <thead> <tr> <th>Outlet Size</th> <th>Nickel Bronze Strainer Head</th> </tr> </thead> <tbody> <tr><td>▲ 02(50)</td><td>05(125) DIA or SQ</td></tr> <tr><td>▲ 03(75)</td><td>06(150) DIA or SQ</td></tr> <tr><td>▲ 04(100)</td><td>08(205) DIA or SQ</td></tr> </tbody> </table> ▼ This dimension to internal stop of speedi-set® gasket. • Add 3/8" (10) to all min/max dimensions for round strainers. * Collar is reversible to obtain extreme high and low strainer positions. •• Not available for 5" (125) size strainer. ** MIN 6 3/4" (170) hole required for core drilled application. SPEEDI-SET® OUTLET ☐ Fig. 2005L(-UDC).....(A) ROUND TOP ☐ Fig. 2005L(-UDC).....(B) SQUARE TOP <table border="1" style="font-size: 0.8em;"> <thead> <tr> <th rowspan="2">Strainer Size B</th> <th colspan="2">*Collar In High Position X</th> <th colspan="2">*Collar In Low Position XX</th> <th colspan="2">Free Area SQ IN (SQ CM)</th> </tr> <tr> <th>DIA or SQ</th> <th>MIN MAX</th> <th>MIN MAX</th> <th>ROUND</th> <th>SQUARE</th> </tr> </thead> <tbody> <tr><td>05 (125)</td><td>1 1/4(32)</td><td>2 1/4(57)</td><td>3/4(19)</td><td>1 5/8(41)</td><td>7(45)</td><td>6.5(42)</td></tr> <tr><td>06 (150)</td><td>1 1/4(32)</td><td>2 1/4(57)</td><td>3/4(19)</td><td>1 5/8(41)</td><td>9(58)</td><td>12.5(81)</td></tr> <tr><td>07 (180)</td><td>1 1/4(32)</td><td>2 1/4(57)</td><td>7/8(22)</td><td>1 7/8(48)</td><td>14(90)</td><td>11(71)</td></tr> <tr><td>08 (205)</td><td>1 1/2(38)</td><td>2 1/2(64)</td><td>1(25)</td><td>1 7/8(48)</td><td>17(110)</td><td>14(90)</td></tr> <tr><td>*09 (230)</td><td>1 1/2(38)</td><td>2 3/8(60)</td><td>1(25)</td><td>1 7/8(48)</td><td>18(116)</td><td>16(103)</td></tr> <tr><td>*10 (255)</td><td>1 1/2(38)</td><td>2 3/8(60)</td><td>1(25)</td><td>1 7/8(48)</td><td>23(48)</td><td>16(103)</td></tr> </tbody> </table>					Outlet Size	Nickel Bronze Strainer Head	▲ 02(50)	05(125) DIA or SQ	▲ 03(75)	06(150) DIA or SQ	▲ 04(100)	08(205) DIA or SQ	Strainer Size B	*Collar In High Position X		*Collar In Low Position XX		Free Area SQ IN (SQ CM)		DIA or SQ	MIN MAX	MIN MAX	ROUND	SQUARE	05 (125)	1 1/4(32)	2 1/4(57)	3/4(19)	1 5/8(41)	7(45)	6.5(42)	06 (150)	1 1/4(32)	2 1/4(57)	3/4(19)	1 5/8(41)	9(58)	12.5(81)	07 (180)	1 1/4(32)	2 1/4(57)	7/8(22)	1 7/8(48)	14(90)	11(71)	08 (205)	1 1/2(38)	2 1/2(64)	1(25)	1 7/8(48)	17(110)	14(90)	*09 (230)	1 1/2(38)	2 3/8(60)	1(25)	1 7/8(48)	18(116)	16(103)	*10 (255)	1 1/2(38)	2 3/8(60)	1(25)	1 7/8(48)	23(48)	16(103)
Outlet Size	Nickel Bronze Strainer Head																																																																	
▲ 02(50)	05(125) DIA or SQ																																																																	
▲ 03(75)	06(150) DIA or SQ																																																																	
▲ 04(100)	08(205) DIA or SQ																																																																	
Strainer Size B	*Collar In High Position X		*Collar In Low Position XX		Free Area SQ IN (SQ CM)																																																													
	DIA or SQ	MIN MAX	MIN MAX	ROUND	SQUARE																																																													
05 (125)	1 1/4(32)	2 1/4(57)	3/4(19)	1 5/8(41)	7(45)	6.5(42)																																																												
06 (150)	1 1/4(32)	2 1/4(57)	3/4(19)	1 5/8(41)	9(58)	12.5(81)																																																												
07 (180)	1 1/4(32)	2 1/4(57)	7/8(22)	1 7/8(48)	14(90)	11(71)																																																												
08 (205)	1 1/2(38)	2 1/2(64)	1(25)	1 7/8(48)	17(110)	14(90)																																																												
*09 (230)	1 1/2(38)	2 3/8(60)	1(25)	1 7/8(48)	18(116)	16(103)																																																												
*10 (255)	1 1/2(38)	2 3/8(60)	1(25)	1 7/8(48)	23(48)	16(103)																																																												
REGULARLY FURNISHED: Duco Cast Iron Body with Flashing Collar, Underdeck Clamp and Adjustable Strainer Head as Indicated by Suffix Letter Selected. NOTE: Dimensions shown in parentheses are in millimeters. ▲ Meets ASME Standard A112.6.3-2001 02(50), 03(75) or 04"(100) sizes only. VARIATIONS: ☐ Flapper Type Backwater Valve -V ☐ Hinged Grate -H ☐ L Speedi-Set® Service Weight 2(50), 3(75) & 4"(100) only ☐ LXH Speedi-Set® Extra Heavy 2(50), 3(75) & 4"(100) only ☐ Sediment Bucket -B ☐ Trap Primer Connection -P050 1/2" (13) & -P075 3/4" (19) ☐ Vandal Proof Screws -U ☐ Wide Flanged Strainer (Specify Fig. DX2005) ☒ Underdeck Clamp -UDC ☐ Quad Close Trap Seal (Specify Fig. 2692) OPTIONAL MATERIALS: ☐ Bronze Body -BB ☐ Chrome Plated Strainer -CP ☐ Galvanized Cast Iron Body -G ☐ Nickel Bronze Strainer -NB ☐ Polished Bronze Strainer -PB ☐ All Stainless Steel (Specify Fig. 9700) ☐ Stainless Steel Strainers -SS [Available in 05(125) & 06(150) sizes only] SEE PM 0457 FOR OPTIONAL STRAINER HEADS.																																																																		
<table border="1" style="width:100%; font-size: 0.8em;"> <tr> <td rowspan="2" style="width:5%; text-align: center; vertical-align: middle;">FIGURE NUMBER</td> <td style="width:10%; text-align: center; vertical-align: middle;">G</td> <td style="width:10%; text-align: center; vertical-align: middle;">8-20-25</td> <td rowspan="2" style="width:30%; text-align: center; vertical-align: middle;">Revised Drawing Chg'd NO-HUB to SPEEDI-SET Added ® to "Speedi-Set" Removed Function</td> <td style="width:10%; text-align: center; vertical-align: middle;">TB</td> <td style="width:10%; text-align: center; vertical-align: middle;">CL</td> <td rowspan="2" style="width:10%; text-align: center; vertical-align: middle;">WEIGHT POUNDS</td> <td rowspan="2" style="width:10%; text-align: center; vertical-align: middle;">VOLUME CUBIC FEET</td> <td rowspan="2" style="width:20%; text-align: center; vertical-align: middle;">FIGURE NUMBER</td> </tr> <tr> <td style="text-align: center; vertical-align: middle;">F</td> <td style="text-align: center; vertical-align: middle;">2-8-24</td> <td style="text-align: center; vertical-align: middle;">HS</td> <td style="text-align: center; vertical-align: middle;">CL</td> </tr> <tr> <td style="text-align: center; vertical-align: middle;">D</td> <td style="text-align: center; vertical-align: middle;">3-10-23</td> <td></td> <td style="text-align: center; vertical-align: middle;">KK</td> <td style="text-align: center; vertical-align: middle;">CL</td> <td></td> <td></td> <td></td> <td rowspan="2" style="text-align: center; vertical-align: middle; font-size: 1.5em; font-weight: bold;">2005(-UDC)</td> </tr> <tr> <td></td> <td style="text-align: center; vertical-align: middle;">6-14-19</td> <td></td> <td style="text-align: center; vertical-align: middle;">MW</td> <td style="text-align: center; vertical-align: middle;">JM</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center; vertical-align: middle;">REV.</td> <td style="text-align: center; vertical-align: middle;">DATE</td> <td style="text-align: center; vertical-align: middle;">DESCRIPTION</td> <td style="text-align: center; vertical-align: middle;">BY</td> <td style="text-align: center; vertical-align: middle;">CKD. BY</td> <td></td> <td></td> <td></td> </tr> </table>					FIGURE NUMBER	G	8-20-25	Revised Drawing Chg'd NO-HUB to SPEEDI-SET Added ® to "Speedi-Set" Removed Function	TB	CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER	F	2-8-24	HS	CL	D	3-10-23		KK	CL				2005(-UDC)		6-14-19		MW	JM					REV.	DATE	DESCRIPTION	BY	CKD. BY																										
FIGURE NUMBER	G	8-20-25	Revised Drawing Chg'd NO-HUB to SPEEDI-SET Added ® to "Speedi-Set" Removed Function	TB		CL	WEIGHT POUNDS		VOLUME CUBIC FEET	FIGURE NUMBER																																																								
	F	2-8-24		HS	CL																																																													
D	3-10-23		KK	CL				2005(-UDC)																																																										
	6-14-19		MW	JM																																																														
	REV.	DATE	DESCRIPTION	BY	CKD. BY																																																													

L						LOCATION																													
OPTIONAL STRAINER HEADS																																			
2010 SERIES OPTIONAL STRAINER HEADS	DRAWING NUMBER	PM0457 SH 1 of 2																																	
	SIZE	A																																	
	SCALE	NONE																																	
	DATE:	5-17-85																																	
	APPROVED BY:	TD																																	
	CHECKED BY:	TD																																	
	DRAWN BY:	PJ																																	
	DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE																																		
	ASSUME NO RESPONSIBILITY OR USE OF SUPERSEDED OR VOID DATA																																		
	2010 SERIES OPTIONAL STRAINER HEADS																																		
FIGURE NUMBER																																			
ROUND STRAINER																																			
		MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB Stainless Steel Strainers -SS [Available in 05(125) & 06(150) sizes only]			VARIATIONS: •Hinged Grate (Specify Suffix -AH) Sediment Bucket -B Vandal Proof Screws -U																														
<table border="1" style="font-size: 8px;"> <tr><th>B DIA</th><th>05 (125)</th><th>06 (150)</th><th>07 (180)</th><th>08 (205)</th><th>09 (230)</th><th>10 (255)</th></tr> <tr><td>H</td><td>2 (51)</td><td>2 (51)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td><td>2 1/2 (64)</td><td>2 3/4 (70)</td></tr> <tr><td>X MIN</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/2 (38)</td><td>1 1/2 (38)</td><td>1 1/2 (38)</td></tr> <tr><td>X MAX</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td><td>2 1/2 (64)</td><td>2 3/4 (70)</td></tr> </table>		B DIA	05 (125)	06 (150)	07 (180)	08 (205)	09 (230)	10 (255)	H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)	X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 1/2 (38)	1 1/2 (38)	X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)	Specify Type, Size & Finish eg: A05NB *Not available for 05" (125) size					
B DIA	05 (125)	06 (150)	07 (180)	08 (205)	09 (230)	10 (255)																													
H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)																													
X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 1/2 (38)	1 1/2 (38)																													
X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)																													
SUFFIX -A																																			
FLAPPER TYPE BACKWATER VALVE																																			
		FUNCTION: Provides backwater protection at point where protection is needed. MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB																																	
<table border="1" style="font-size: 8px;"> <tr><th>B SQ</th><th>05 (125)</th><th>06 (150)</th><th>07 (180)</th><th>08 (205)</th></tr> <tr><td>H</td><td>2 (51)</td><td>2 (51)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td></tr> <tr><td>X MIN</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/2 (38)</td></tr> <tr><td>X MAX</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td></tr> </table>		B SQ	05 (125)	06 (150)	07 (180)	08 (205)	H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	Specify Type, Size & Finish eg: AV05NB *Not available for 05" (125) size													
B SQ	05 (125)	06 (150)	07 (180)	08 (205)																															
H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)																															
X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)																															
X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)																															
SUFFIX -AV																																			
SQUARE STRAINER																																			
		MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB			VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -BV) 05 (125), 06 (150), 07 (180) or 08" (205) sizes only *Hinged Grate (Specify Suffix -BH) Sediment Bucket -B Vandal Proof Screws -U																														
<table border="1" style="font-size: 8px;"> <tr><th>B SQ</th><th>05 (125)</th><th>06 (150)</th><th>07 (180)</th><th>08 (205)</th><th>09 (230)</th><th>10 (255)</th></tr> <tr><td>H</td><td>2 (51)</td><td>2 (51)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td></tr> <tr><td>X MIN</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/2 (38)</td><td>1 1/2 (38)</td><td>1 1/2 (38)</td></tr> <tr><td>X MAX</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td><td>2 1/4 (57)</td><td>2 3/8 (60)</td></tr> </table>		B SQ	05 (125)	06 (150)	07 (180)	08 (205)	09 (230)	10 (255)	H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	2 1/4 (57)	X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 1/2 (38)	1 1/2 (38)	X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	2 3/8 (60)	Specify Type, Size & Finish eg: B05NB *Not available for 05" (125) size					
B SQ	05 (125)	06 (150)	07 (180)	08 (205)	09 (230)	10 (255)																													
H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	2 1/4 (57)																													
X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 1/2 (38)	1 1/2 (38)																													
X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	2 3/8 (60)																													
SUFFIX -B																																			
STRAINER HEAD w/SQUARE HINGED COVER																																			
		MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB			VARIATIONS: Gasketed Water Tight Cover -GC Secured Cover -SC Secondary Strainer Grate-SG																														
<table border="1" style="font-size: 8px;"> <tr><th>SUFFIX</th><th>B DIA</th><th>H</th><th>X MIN</th><th>X MAX</th></tr> <tr><td>-D</td><td>07 (180)</td><td>3 1/4 (83)</td><td>2 5/8 (67)</td><td>3 1/2 (89)</td></tr> <tr><td>-E</td><td>09 (230)</td><td>3 1/2 (89)</td><td>2 3/4 (70)</td><td>3 1/2 (89)</td></tr> </table>		SUFFIX	B DIA	H	X MIN	X MAX	-D	07 (180)	3 1/4 (83)	2 5/8 (67)	3 1/2 (89)	-E	09 (230)	3 1/2 (89)	2 3/4 (70)	3 1/2 (89)	Specify Type, Size & Finish eg: BS0NB																		
SUFFIX	B DIA	H	X MIN	X MAX																															
-D	07 (180)	3 1/4 (83)	2 5/8 (67)	3 1/2 (89)																															
-E	09 (230)	3 1/2 (89)	2 3/4 (70)	3 1/2 (89)																															
SUFFIX -BS																																			
REINFORCED ROUND STRAINER																																			
FUNCTION: Used in finished floors where light wheeled loads are anticipated.																																			
		MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB			VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -CV) Sediment Bucket -B Vandal Proof Screws -U																														
<table border="1" style="font-size: 8px;"> <tr><th>B DIA</th><th>05 (125)</th><th>06 (150)</th><th>08 (205)</th><th>10 (255)</th></tr> <tr><td>H</td><td>2 (51)</td><td>2 (51)</td><td>2 1/2 (64)</td><td>2 3/4 (70)</td></tr> <tr><td>MIN</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/2 (38)</td><td>1 7/8 (48)</td></tr> <tr><td>MAX</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td><td>2 3/4 (70)</td></tr> </table>		B DIA	05 (125)	06 (150)	08 (205)	10 (255)	H	2 (51)	2 (51)	2 1/2 (64)	2 3/4 (70)	MIN	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 7/8 (48)	MAX	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 3/4 (70)	Specify Type, Size & Finish eg: C06NB													
B DIA	05 (125)	06 (150)	08 (205)	10 (255)																															
H	2 (51)	2 (51)	2 1/2 (64)	2 3/4 (70)																															
MIN	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 7/8 (48)																															
MAX	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 3/4 (70)																															
SUFFIX -C																																			
REINFORCED TRACTOR STRAINER																																			
FUNCTION: Used in finished floors where light weight wheeled loads are anticipated and loose set non-tilt tractor grate is desired.																																			
		MATERIALS: Cast Iron -CI Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB			VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -DV or -EV) Sediment Bucket -B Vandal Proof Screws -U																														
<table border="1" style="font-size: 8px;"> <tr><th>SUFFIX</th><th>B DIA</th><th>H</th><th>X MIN</th><th>X MAX</th></tr> <tr><td>-D</td><td>07 (180)</td><td>3 1/4 (83)</td><td>2 5/8 (67)</td><td>3 1/2 (89)</td></tr> <tr><td>-E</td><td>09 (230)</td><td>3 1/2 (89)</td><td>2 3/4 (70)</td><td>3 1/2 (89)</td></tr> </table>		SUFFIX	B DIA	H	X MIN	X MAX	-D	07 (180)	3 1/4 (83)	2 5/8 (67)	3 1/2 (89)	-E	09 (230)	3 1/2 (89)	2 3/4 (70)	3 1/2 (89)	Specify Type, Size & Finish eg: D07PB E09PB																		
SUFFIX	B DIA	H	X MIN	X MAX																															
-D	07 (180)	3 1/4 (83)	2 5/8 (67)	3 1/2 (89)																															
-E	09 (230)	3 1/2 (89)	2 3/4 (70)	3 1/2 (89)																															
SUFFIX -D-E																																			
TILE FLANGE																																			
FUNCTION: Provides integral flange set 5/32"(4) below rim to receive floor covering. Flange may have option of tapped holes for securing pan and gasket.																																			
		MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB			VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -FV) Holes in Flange -SH Sediment Bucket -B Vandal Proof Screws -U																														
<table border="1" style="font-size: 8px;"> <tr><th>SUFFIX</th><th>B DIA</th><th>H</th><th>X MIN</th><th>X MAX</th></tr> <tr><td>-F</td><td>07 (180)</td><td>3 1/4 (83)</td><td>2 5/8 (67)</td><td>3 1/2 (89)</td></tr> <tr><td>-G</td><td>09 (230)</td><td>3 1/2 (89)</td><td>2 3/4 (70)</td><td>3 1/2 (89)</td></tr> </table>		SUFFIX	B DIA	H	X MIN	X MAX	-F	07 (180)	3 1/4 (83)	2 5/8 (67)	3 1/2 (89)	-G	09 (230)	3 1/2 (89)	2 3/4 (70)	3 1/2 (89)	Specify Type, Size & Finish eg: F06NB																		
SUFFIX	B DIA	H	X MIN	X MAX																															
-F	07 (180)	3 1/4 (83)	2 5/8 (67)	3 1/2 (89)																															
-G	09 (230)	3 1/2 (89)	2 3/4 (70)	3 1/2 (89)																															
SUFFIX -F																																			
ADJUSTABLE STRAINER HEAD																																			
FUNCTION: Used in a non-traffic area when a funnel type strainer head is required and space does not allow use of the 3500 series funnel. The extended rim allows use as an anti-flood and anti-splash drip pan.																																			
		VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -F37V or F38V)			MATERIALS: Cast Iron -CI Chrome Plated -CP Galvanized Cast Iron -G Polished Bronze -PB Nickel Bronze -NB																														
<table border="1" style="font-size: 8px;"> <tr><th>SUFFIX</th><th>B DIA</th><th>H</th><th>X MIN</th><th>X MAX</th></tr> <tr><td>-F37</td><td>07 (180)</td><td>3 1/4 (83)</td><td>2 5/8 (67)</td><td>3 1/2 (89)</td></tr> <tr><td>-F38</td><td>09 (230)</td><td>3 1/2 (89)</td><td>2 3/4 (70)</td><td>3 1/2 (89)</td></tr> </table>		SUFFIX	B DIA	H	X MIN	X MAX	-F37	07 (180)	3 1/4 (83)	2 5/8 (67)	3 1/2 (89)	-F38	09 (230)	3 1/2 (89)	2 3/4 (70)	3 1/2 (89)	Specify Type, Size & Finish eg: F37NB F38CP																		
SUFFIX	B DIA	H	X MIN	X MAX																															
-F37	07 (180)	3 1/4 (83)	2 5/8 (67)	3 1/2 (89)																															
-F38	09 (230)	3 1/2 (89)	2 3/4 (70)	3 1/2 (89)																															
SUFFIX -F37-F38																																			
FIGURE NUMBER																																			
2010 SERIES OPTIONAL STRAINER HEADS																																			
1 of 2																																			

NOTE: Dimensions shown in parentheses are in millimeters.



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

DRAWING NUMBER PM0457 SH 2 of 2	SIZE A	NONE	SCALE	DATE: 5-17-85	APPROVED BY: TD	CHECKED BY: TD	DRAWN BY: PJ	2010 SERIES OPTIONAL STRAINER HEADS	DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com				   MEMBER OF:				LOCATION																																																																				
										OPTIONAL STRAINER HEADS																																																																												
										LOW DOME STRAINER				SOLID HINGED COVER				SPANNER WRENCH COVER																																																																				
										FUNCTION: Used in gutters and recessed areas where excessive debris build-up is expected. Dome insures drainage even when partly covered. MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -GV) Sediment Bucket -B Vandal Proof Screws -U  <table><tr><td>B DIA</td><td>05 (125)</td><td>06 (150)</td><td>08 (205)</td></tr><tr><td>H</td><td>2 (51)</td><td>2 (51)</td><td>2 1/2 (64)</td></tr><tr><td>MIN</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/2 (38)</td></tr><tr><td>MAX</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td></tr></table> SUFFIX -G Specify Type, Size & Finish eg: G08PB				B DIA	05 (125)	06 (150)	08 (205)	H	2 (51)	2 (51)	2 1/2 (64)	MIN	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	MAX	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	FUNCTION: Used in areas where intermittent drain use is required. Solid cover prevents intrusion of chips, saw-dust, etc., which are swept up before cover is opened for washdown. The secondary strainer prevents debris from entering the waste line. MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -GV) Vandal Proof Screws -U  <table><tr><td>B DIA</td><td>05 (125)</td><td>06 (150)</td><td>07 (180)</td><td>08 (205)</td></tr><tr><td>H</td><td>2 (51)</td><td>2 (51)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td></tr><tr><td>MIN</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/2 (38)</td></tr><tr><td>MAX</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td></tr></table> SUFFIX -H Specify Type, Size & Finish eg: H05CP				B DIA	05 (125)	06 (150)	07 (180)	08 (205)	H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	FUNCTION: Solid gas tight, vandal proof, threaded cover for areas where intermittent drain use is required. MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -JV) Sediment Bucket -B  <table><tr><td colspan="2">MEDIUM DUTY</td></tr><tr><td>MIN</td><td>MAX</td></tr><tr><td>2 (51)</td><td>3 (76)</td></tr></table> SUFFIX -J Specify Type, Size & Finish eg: J06NB						MEDIUM DUTY		MIN	MAX	2 (51)	3 (76)																					
										B DIA	05 (125)	06 (150)	08 (205)																																																																									
										H	2 (51)	2 (51)	2 1/2 (64)																																																																									
										MIN	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)																																																																									
										MAX	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)																																																																									
										B DIA	05 (125)	06 (150)	07 (180)	08 (205)																																																																								
										H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)																																																																								
MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)																																																																																		
MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)																																																																																		
MEDIUM DUTY																																																																																						
MIN	MAX																																																																																					
2 (51)	3 (76)																																																																																					
REINFORCED SQUARE STRAINER				RECTANGULAR STRAINER				ANGLE STRAINER																																																																														
FUNCTION: Used in finished floors where some light wheeled traffic is anticipated. MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -KV) Sediment Bucket -B Vandal Proof Screws -U  <table><tr><td>B SQ</td><td>05 (125)</td><td>06 (150)</td><td>07 (180)</td><td>08 (205)</td></tr><tr><td>H</td><td>2 (51)</td><td>2 (51)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td></tr><tr><td>MIN</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/2 (38)</td></tr><tr><td>MAX</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td></tr></table> SUFFIX -K Specify Type, Size & Finish eg: K07CP				B SQ	05 (125)	06 (150)	07 (180)	08 (205)	H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	FUNCTION: Used in finished floors where light wheeled loads and or heavy foot traffic are anticipated. MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Sediment Bucket -B Vandal Proof Screws -U  <table><tr><th>SUFFIX</th><th>L</th><th>M</th><th>N</th><th>P</th><th>R</th><th>T</th></tr><tr><td>B x B</td><td>4 1/2 (115)</td><td>4 1/2 (115)</td><td>5 (125)</td><td>5 (125)</td><td>6 (150)</td><td>5 (125)</td></tr><tr><td>H</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td><td>2 1/4 (57)</td><td>3 (76)</td><td>2 1/4 (57)</td><td>3 (76)</td></tr><tr><td>MIN</td><td>1 3/8 (35)</td><td>1 7/8 (48)</td><td>1 3/8 (35)</td><td>2 1/8 (54)</td><td>1 3/8 (35)</td><td>2 1/4 (57)</td></tr><tr><td>MAX</td><td>2 3/8 (60)</td><td>2 3/4 (70)</td><td>2 3/8 (60)</td><td>3 (76)</td><td>2 3/8 (60)</td><td>3 1/8 (79)</td></tr></table> SUFFIX -L-M-N-P-R-T Specify Type, Size & Finish eg: LNB				SUFFIX	L	M	N	P	R	T	B x B	4 1/2 (115)	4 1/2 (115)	5 (125)	5 (125)	6 (150)	5 (125)	H	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	3 (76)	2 1/4 (57)	3 (76)	MIN	1 3/8 (35)	1 7/8 (48)	1 3/8 (35)	2 1/8 (54)	1 3/8 (35)	2 1/4 (57)	MAX	2 3/8 (60)	2 3/4 (70)	2 3/8 (60)	3 (76)	2 3/8 (60)	3 1/8 (79)	FUNCTION: Shower room drain set at wall and floor junction. Vertical grate openings prevent drain stoppage should flat surface become covered. MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Vandal Proof Screws -U  <table><tr><th>SUFFIX</th><th>B</th><th>C</th><th>D</th><th>MIN</th><th>MAX</th></tr><tr><td>-V</td><td>3 1/2 (89)</td><td>3 1/2 (89)</td><td>4 1/2 (115)</td><td>1 5/8 (41)</td><td>2 5/8 (67)</td></tr><tr><td>-W</td><td>6 3/4 (170)</td><td>6 3/4 (170)</td><td>6 1/2 (165)</td><td>1 5/8 (41)</td><td>2 5/8 (67)</td></tr></table> SUFFIX -V-W Specify Type, Size & Finish eg: VPB, WNB						SUFFIX	B	C	D	MIN	MAX	-V	3 1/2 (89)	3 1/2 (89)	4 1/2 (115)	1 5/8 (41)	2 5/8 (67)	-W	6 3/4 (170)	6 3/4 (170)	6 1/2 (165)	1 5/8 (41)	2 5/8 (67)
B SQ	05 (125)	06 (150)	07 (180)	08 (205)																																																																																		
H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)																																																																																		
MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)																																																																																		
MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)																																																																																		
SUFFIX	L	M	N	P	R	T																																																																																
B x B	4 1/2 (115)	4 1/2 (115)	5 (125)	5 (125)	6 (150)	5 (125)																																																																																
H	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	3 (76)	2 1/4 (57)	3 (76)																																																																																
MIN	1 3/8 (35)	1 7/8 (48)	1 3/8 (35)	2 1/8 (54)	1 3/8 (35)	2 1/4 (57)																																																																																
MAX	2 3/8 (60)	2 3/4 (70)	2 3/8 (60)	3 (76)	2 3/8 (60)	3 1/8 (79)																																																																																
SUFFIX	B	C	D	MIN	MAX																																																																																	
-V	3 1/2 (89)	3 1/2 (89)	4 1/2 (115)	1 5/8 (41)	2 5/8 (67)																																																																																	
-W	6 3/4 (170)	6 3/4 (170)	6 1/2 (165)	1 5/8 (41)	2 5/8 (67)																																																																																	
EXTENSION ADAPTOR				OVERFLOW WITH STANDPIPE				HEAVY DUTY ADJUSTABLE																																																																														
FUNCTION: Used when a strainer head must be raised to accommodate deeper floor fill. REGULARLY FURNISHED: Ducto Cast Iron -CI MATERIALS: Cast Bronze -CB Galvanized Cast Iron -G  NOTE: Extension can be stacked for increased maximum adjustment. SUFFIX -X				FUNCTION: Used as overflow drain in decorative pools, fish ponds or similar areas. Dome prevents floating objects from entering drain line. MATERIALS: Chrome Plated -CP Nickel Bronze -NB Polished Bronze -PB VARIATIONS: Less Dome -LD Standpipe Height other than 6" (150) (Specify Height)  <table><tr><th>SUFFIX</th><th>A SIZE</th><th>MIN</th><th>MAX</th></tr><tr><td>-Y</td><td>2 (51)</td><td>3/4 (19)</td><td>2 1/8 (54)</td></tr><tr><td>-Z</td><td>3 (76)</td><td>3/4 (19)</td><td>2 1/8 (54)</td></tr></table> SUFFIX -Y-Z Specify Type, Size & Finish eg: YCP, ZCP				SUFFIX	A SIZE	MIN	MAX	-Y	2 (51)	3/4 (19)	2 1/8 (54)	-Z	3 (76)	3/4 (19)	2 1/8 (54)	FUNCTION: Used in finished floors where light wheeled loads and or heavy foot traffic are anticipated. MATERIALS: Polished Bronze -PB Rough Bronze -RB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -69V) Sediment Bucket -B Vandal Proof Screws -U  SUFFIX -69 eg: A06NB-69																																																																		
SUFFIX	A SIZE	MIN	MAX																																																																																			
-Y	2 (51)	3/4 (19)	2 1/8 (54)																																																																																			
-Z	3 (76)	3/4 (19)	2 1/8 (54)																																																																																			
   																																																																																						
<table><tr><td>L</td><td>7-29-19</td><td rowspan="5">Added Load Rating(s) Rev. Materials Suffix -H, -V-W Rev. Variations of Suffix -J Revised Revised Tables</td><td>MW</td><td>JM</td></tr><tr><td>K</td><td>10-20-17</td><td>TBW</td><td>CL</td></tr><tr><td>J</td><td>1-17-12</td><td>TBW</td><td>AM</td></tr><tr><td>H</td><td>8-24-99</td><td>TBW</td><td>BS</td></tr><tr><td>G</td><td>6-11-99</td><td>CMD</td><td></td></tr></table>														L	7-29-19	Added Load Rating(s) Rev. Materials Suffix -H, -V-W Rev. Variations of Suffix -J Revised Revised Tables	MW	JM	K	10-20-17	TBW	CL	J	1-17-12	TBW	AM	H	8-24-99	TBW	BS	G	6-11-99	CMD																																																					
L	7-29-19	Added Load Rating(s) Rev. Materials Suffix -H, -V-W Rev. Variations of Suffix -J Revised Revised Tables	MW	JM																																																																																		
K	10-20-17		TBW	CL																																																																																		
J	1-17-12		TBW	AM																																																																																		
H	8-24-99		TBW	BS																																																																																		
G	6-11-99		CMD																																																																																			
<table><tr><th>REV.</th><th>DATE</th><th>DESCRIPTION</th><th>BY</th><th>CKD. BY</th></tr><tr><td>L</td><td>7-29-19</td><td></td><td></td><td></td></tr><tr><td>K</td><td>10-20-17</td><td></td><td></td><td></td></tr><tr><td>J</td><td>1-17-12</td><td></td><td></td><td></td></tr><tr><td>H</td><td>8-24-99</td><td></td><td></td><td></td></tr><tr><td>G</td><td>6-11-99</td><td></td><td></td><td></td></tr></table>														REV.	DATE	DESCRIPTION	BY	CKD. BY	L	7-29-19				K	10-20-17				J	1-17-12				H	8-24-99				G	6-11-99																																														
REV.	DATE	DESCRIPTION	BY	CKD. BY																																																																																		
L	7-29-19																																																																																					
K	10-20-17																																																																																					
J	1-17-12																																																																																					
H	8-24-99																																																																																					
G	6-11-99																																																																																					
FIGURE NUMBER																																																																																						
2010 SERIES OPTIONAL STRAINER HEADS																																																																																						
2 of 2																																																																																						

NOTE: Dimensions shown in parentheses are in millimeters.



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov